INDEX

abbreviated precision registration, 5-21, 5-22	authentication, 4-6
AC-130 Spectre, A-16	challenge and reply method, 4-7
accurate initial fires, 1-2	DMD, using the, B-8 through B-13
adjust fire (mission type), 4-1	FED, using the, B-18
adjusting point, 5-1	transmission authentication method, 4-6, 4-7
adjustment	auxiliary adjusting point, use of, 7-10, A-9 through A-11
AN/GVS-5, using the, A-14	
DMD, using the, B-6, B-7, B-14 through B-17	battery computer system (BCS) sheaf, 4-4
G/VLLD, using the, A-8, A-9	binoculars, use of to measure angular deviations, 3-5
length of, 1-2	
naval gunfire, of, 8-13, 8-14	call for fire, 4-1
sound, by, 7-11, 7-12 techniques of (AFSO), 7-2	changes to, 4-6
techniques of (AFSO), 7-2 techniques of (area fire), 5-8 through 5-10	DMD, using a, B-13, B-14
types of, 4-3	elements of, 4-1
aerial fire support observer, 7-1 through 7-3	examples of, 4-7
AH-64 target acquisition and designation sight, A-14, A-15	from higher headquarters, 4-6 naval gunfire, for, 8-8 through 8-11
aiming circle, 3-4, 7-7, 7-8	cannot observe (method of control), 4-5
determining direction with, 3-4	cease loading (method of control), 4-5
aiming points, E-6	centralized control option, 2-3
ammunition	C factor, 7-12
as method of engagement, 4-4	challenge and reply
selecting suitable, E-5	authentication method, 4-6
Angle T, 4-6, 5-5, 6-23, 6-24	using a DMD, B-10
angular deviations	check firing (method of control), 4-5
measuring, 3-5	close air support, 2-1, 8-1 through 8-6
measuring with hand, 3-11	attack information for, 8-1, 8-2
AN/GVS-5 laser range finder, 5-24, A-13, A-14	control measures for, 8-1
adjustment of fire with, A-14	employment of, 8-1 through 8-3
self-location with, A-14	marking of target for, 8-3
AN/PAQ-1 laser target designator, A-15	mission control procedures for, 8-3 through 8-6 mission data for, 8-1, 8-2
AN/TAS-4 night vision sight, A-1, A-2, A-12, A-13	PRF codes for, 8-3
ranging and designating with, A-12	types of requests for, 8-1
training with, A-13	combined arms team integrated evaluation system, C-3
APICM, 6-1	communications, 2-5, 8-8
area adjustment, 4-4	digital, establishing with the DMD, B-6
area denial artillery munition (ADAM) shell, 4-11	with the FED, B-20
area fire, 5-8 through 5-11	company FSO, 2-2
at my command (method of control), 4-4	compass, determining direction with, 3-4
attack and scout teams, 8-6	conduct of fire form (DA Form 5429-R), 4-1
attack helicopters, 8-6, 8-7	continuous fire (method of control), 4-5
capabilities of, 8-6	continuous illumination (method of control), 4-5, 6-10
employment of, 8-6	control of observers, 2-3
target handover for, 8-6, 8-7	converged sheaf, 4-4

coordinated illumination (method of control), 4-5, 6-10	dual-purpose ICM, 4-11, 6-1
Copperhead, 5-22, 5-23, 5-25, 6-22 through 6-27	
Angle T requirements for, 6-23, 6-24	effects on target, 4-9
call for fire for, 6-25 through 6-27	•
characteristics of, 6-22	emergency observer procedures, 7-12
employment of, 6-22	errors, correction of during call for fire, 4-5
engagement commands, 6-27	
footprint templates for, 6-22 through 6-24	family of scatterable mines (FASCAM), 6-3 through 6-7
laser PRF codes for, 6-27	ADAM, 4-11, 6-3, 6-4
message to observer, 6-27	adjustment of, 6-7
minimum visibility requirements for, 6-22	call for fire for, 6-7
planned targets, 6-25, 6-26	characteristics of, 6-3
priority targets, 6-26	mine density, 6-5
procedures using FED, B-26	minefield types, 6-4
targets of opportunity, 6-24 through 6-26	RAAMS, 4-11, 6-3
correction of errors, 4-5	self-destruction times, 4-11, 6-3 through 6-5
creeping fire, 5-10	use of shell, 4-11
	field artillery team, 1-1
danger close (method of engagement), 4-4, 5-6, 5-10, 6-2,	field artillery trainer M31, 14.5-mm, C-2, C-3
7-4, 8-9	final protective fires, 7-4, 7-5, B-26, B-27
decentralized control option, 2-3	fire direction center, 1-1
deception smoke, 6-12	fire for effect (area fire), 5-10, 5-11
delay (fuze setting), 4-9	fire for effect (mission type), 4-1
destruction	firepower control team (FCT), 2-1
as effect on target, 4-9	• //
naval gunfire mission, 8-18	fires
precision fire mission, 4-3, 5-22	accurate initial, 1-2
deviation corrections, 5-4, 5-5, 5-7	massed, 1-3
deviation spottings, 5-3	fire support
digital communications, 2-5, B-6, B-20	coordinator (FSCOORD), 1-5
direction, determining, 3-4	effectiveness of, 1-2 sergeant, 2-2
distance, determining, 3-6	specialist, 2-2
distribution (method of engagement), 4-4, 5-6, 5-7	team, 2-1
DMD AN/PSG-2A, B-1 through B-17, D-1 through D-3	team equipment, 2-1
authentication codes for, B-6, B-8 through B-12	* *
authentication with, B-8 through B-12	fire support team vehicle (FISTV), D-1 through D-3
description of, B-1	capabilities of, D-1
diagnostic checks for, B-5	communications station, D-1, D-2 description of, D-1
establishing communications with, B-6	determining target location with, D-2
functional sections of, B-1 through B-4	determining vehicle location with, D-2
memory capacity of, B-1	observation station, D-2
memory purge of, B-5	positioning, 2-4, 2-5
message composition and transmission, B-12	targeting station, D-1
through B-17	firing unit, 1-1
message formats of, B-6, B-7	
message structure, composition, and flow, B-7, B-8	first-round FFE, 1-5
mnemonics for, B-34 through B-38	FIST DMD, B-29 through B-31, D-1 through D-3
mode menu for, B-6, B-7	description of, B-31
preparation for use of, B-5, B-6	mnemomics for, B-34 through B-38
purging memory of, B-11	operation of, B-29, B-30
special-purpose power sources for, B-33, B-34	flash-to-bang technique, 3-6

forward air controller, 2-1	Hellfire
forward entry device (FED), B-18 through B-28	missile, 8-6, A-14
authentication procedures for, B-18	ground support system (training device), C-3
check fire and cancel check fire procedures, B-28	high-angle fire, 7-3
communications, B-20	high-burst/mean-point-of-impact registrations, 7-7 through
communications, failure of, B-22	7-10, B-15, B-16, B-25, B-26
description of, B-18 fire mission processing procedures, B-24 through B-28	high-explosive (HE)
initialization of, B-20, B-21	fuze concrete piercing, use with, 4-10
memory capacity of, B-18	fuze delay, use with, 4-9
message formats, B-18 through B-20	fuze quick, use with, 4-9
message processing procedures for, B-23, B-24	fuze time, use with, 4-10
message transfer modes, B-20	fuze VT, use with, 4-10
mnemomics for, B-34 through B-38	shell, 4-9
operational checks for, B-20	
power failure of, B-22	ICM, 6-1 through 6-3
preparation for use, B-20 through B-22	adjustment of, 6-1, 6-2
self-location, calculating with, B-21, B-22	call for fire for, 6-1
transferring software data with, B-23	characteristics of, 6-1
forward observer, 2-2	employment considerations of, 6-3
control of, 2-3	identification, observer (CFF element), 4-1
self-location, 2-4	illuminating shell, 4-11
fuze (method of engagement), 4-4, 5-7	illumination, 6-7 through 6-11
fuzes, selection considerations, 4-9	adjustment of, 6-9
	call for fire for, 6-9
grid	characteristics of, 6-7
method of target location, 3-1, 4-2	continuous, 6-10
mission, 4-2, B-13	coordinated, 6-10
G/VLLD, 3-4, A-1 through A-13, D-1	employment considerations of, 6-7 through 6-9
adjustment of fire with, A-8, A-9	naval gunfire, 8-14 through 8-16
AN/TAS-4 night vision sight, use with, A-1, A-2, A-12,	patterns, 6-7 through 6-9
A-13	immediate smoke, 6-14, 6-18, 6-19
auxiliary adjusting point with, A-9 through A-11	immediate suppression (mission type), 4-2
boresighting of, A-2	impact registration, 5-12 through 5-15
description of, A-1, A-2	improved conventional munitions (ICM), 4-11
determining direction with, 3-4	intercept point, 5-23 through 5-25
establishing known points with, A-5	
laser training kit, C-2, C-3	irregularly shaped targets, 7-10, 7-11
operator cloud height, A-11	
orienting, A-2	joint air attack teams, 8-6
polar plot with, A-7, A-8	
registrations with, A-12	known point
safety fan and range safety card, A-18 through A-20	shift from, 4-2
second G/VLLD assist of, A-5 through A-7	determining with G/VLLD, A-5
self-location with, A-2 through A-5	<i>5</i> ,
simultaneous observation with, A-6, A-7	locar 1 5 2 6 A 1 4 hours 1 A 20
TSFO-G/VLLD simulation enhancement, C-2	laser, 1-5, 3-6, A-1 through A-20
	DMD messages for use with a, B-14, B-15, B-17
hand measurement of angular deviation, 3-11	safety, A-16 through A-20 safety goggles, A-17
hasty bracketing, 5-9, 5-10	target designation, 4-11
height-of-burst corrections, 5-5, 5-7	target designation, 4-11 target designator AN/PAQ-1, A-15
height-of-burst spottings, 5-1, 5-2	training kit G/VIID C-2 C-3

used to determine distance, 3-6 use on the battlefield, A-1 laser-guided	mortar ballistic computer M23, B-32 registration, 5-15
bombs, A-16	sheaf adjustment, 5-15, 5-16
munitions, A-1, A-16 laser polar plot, 4-2	smoke procedures, 6-21 moving targets
laser range finder, 1-5 AN/GVS-5, 5-24, A-13, A-14 used to measure angular deviation, 3-4, 3-5	engagement of, 5-23 through 5-25 planned targets, 5-25 procedures using FED, B-27, B-28
lateral shift, determining, 3-2	targets of opportunity, 5-23 through 5-25
law of war, 1-4	M31 14.5-mm field artillery trainer, C-2, C-3 multiple missions, 7-5, 7-6
lithium batteries, B-33, B-34	munitions, 1-4
lost spottings, 5-3, 5-4	munitions, 1-4
low-altitude navigation and targeting infrared system (LANTIRN), A-16	naval gunfire, 8-7 through 8-19 adjustment of, 8-13, 8-14 authentication for, 8-11
maneuver commander, 1-5	communications for, 8-8
map	destruction fire missions, 8-18
determining direction from, 3-4	dispersion pattern of, 8-13
-terrain analysis, 3-7	elements of call for fire for, 8-8 through 8-11
marking targets for CAS, 8-3	firing on a previously recorded target, 8-17 illumination, 8-14 through 8-16
mark (method of engagement), 4-4	massed fires, 8-18
massed fires, 1-3	prefiring report for, 8-11, 8-15
massing of naval gunfire, 8-18	shift to a fresh target, 8-16, 8-17
mast-mounted sight (OH-58D), A-15	ship and armament types for, 8-7
matchbox problem (training device), C-1	simultaneous engagement of two targets, 8-17 16-inch missions, 8-18
nessage formats for the DMD, B-6, B-7	special commands and reports, 8-18, 8-19
for the FED, B-18 through B-20	neutralization (effect on target), 4-9
nessage to observer, 4-6	night observation system (NOS) OV-10D, A-16
nessage transfer modes, FED, B-20	night vision sight AN/TAS-4, A-1, A-2, A-12, A-13
nethod	number of rounds (element of MTO), 4-6
of attack, selecting, E-6	·
of control, 4-5, 5-7	obscuring smoke, 6-12, 6-13
of engagement, 4-3	observation, 2-4
of fire, 4-4, 5-6	observation post
of fire and control, 4-4	characteristics, 2-4
nil relation formula, 3-2, 3-7	selection of, 2-3
nine density, FASCAM, 6-5	observed fire (OF) fan, 3-7, 3-9
ninefield types, FASCAM, 6-4	preparation and use of, 3-10
planned, 6-4 target of opportunity, 6-4	observer
nines, FASCAM, 4-11, 6-3 through 6-7	emergency procedures, 7-12
	helpful notes for, 5-26 identification (CFF element), 4-1
nissions, types of, 4-1	not oriented, 7-10
nission type, subsequent correction of, 5-7	responsibilities in target analysis and munitions
nnemonics for digital devices, B-34 through B-38	effects, E-1
nodular universal laser equipment (MULE), 6-22, A-15, A-16	observer-target direction, 3-2, 5-6

Index-4

distance, 3-9, 5-4	precision, 5-12 through 5-22, A-12, B-15, B-25
factor, 5-4 line, 5-1 through 5-3, 5-5, 5-12	radar, B-16
observer training for nonartillery personnel, C-3, C-4	remote antiarmor mine system (RAAMS) shell, 4-11
OH-58D mast-mounted sight, A-15	repeat (method of control), 4-5, 5-8
one-round adjustment, 5-10	responsibilites, 2-2
open sheaf, 4-4	ricochet fire, 4-9
operator cloud height, A-11	
operator's key (for DMD authentication), B-6	safety fan, G/VLLD, A-18 through A-20
OV-10D night observation system (NOS), A-16	safety, laser, A-16 through A-20
0 V-1012 hight observation system (1005), A-10	screening smoke, 6-12, 6-13
D D 446	second-lot registration, 5-21
Pave Penny, A-16	self-authentication, 4-7
Pave Spike, A-16	using a DMD, B-8, B-9
Pave Tack, A-16	self-location, 1-4, A-2 through A-5
Paveway II and III laser-guided bombs, A-16	with AN/GVS-5, A-13
planned targets for Copperhead, 6-25, 6-26	with FED, B-21, B-22
polar plot	with G/VLLD, A-2 through A-5
method of location, 3-1, 4-2 mission, 4-3, B-14, B-17	shell-fuze combination, 1-4, 4-9
position-locating system,1-5, 3-1	shift from known point
power sources, special purpose, for DMD and FIST	method of target location, 3-1, 3-2, 4-2
DMD, B-33, B-34	mission type, 4-2, B-13 through B-15 sheafs, 4-4
precision fire (type of adjustment), 4-3, 5-12 through 5-22	signaling smoke, 6-12
precision registration, 5-12 through 5-22, B-15, B-25	size of element to fire for effect (element of warning
predesignated control option, 2-3	order), 4-2
PRF codes, 4-11, 6-27, 8-3, A-1	smoke, 6-12 through 6-21
for CAS, 8-3	characteristics of, 6-12, 6-13
for Copperhead, 6-27	for deception, 6-12
probable error in range (element of MTO), 4-6, 5-10, 5-12	delivery techniques of, 6-13, 6-14
projectile (method of engagement), 4-4, 5-7	employment considerations for, 6-14 through 6-18
proximity (VT) fuze, use with HE, 4-10	immediate, 6-14, 6-18, 6-19
	mortar procedures, 6-21
quick fuze, use with HE, 4-9	non-field-artillery, 6-13 obscurating, 6-12, 6-13
quick smoke, 6-20, 6-21	quick, 6-20, 6-21
quick smoke, 0-20, 0-21	screening, 6-12, 6-13
	shell, 4-11
radar registration, B-16	signaling, 6-12
radio telephone operator (RATELO), 2-2	sound, speed of, 7-12
range change, determining, 3-3	Spectre, AC-130, A-16
range corrections, 5-5, 5-7	splash (method of control), 5-8
range safety card, G/VLLD, A-18 through A-20	spotting lines (for AFSO), 7-1, 7-2
range spottings, 5-2	spottings, types of, 5-1 through 5-4
reconnaissance, 2-4	subsequent corrections, 5-1 through 5-8, B-14, B-15, D-2,
reference point, measuring direction from, 3-4	D-3
refinement and surveillance (area fire), 5-11	deviation, 5-4, 5-5, 5-7
registrations	height of burst, 5-5, 5-7
abbreviated (using G/VLLD), A-12	range, 5-5, 5-7
HB/MPI, 7-7 through 7-10, A-12,B-15, B-16,	sequence for, 5-6 through 5-8
B-25, B-26	types of, 5-4, 5-5

successive bracketing, 5-8, 5-9	technical fire direction, 1-1
suppression	temperature gradients 6-14, 6-15
as effect on target, 4-9	time fuze, use with HE, 4-10
type of mission, 4-2	time of flight (element of MTO), 4-6
	time on target (TOT), 4-4, 4-5
TACFIRE target types, E-1 through E-3	time registration, 5-16 through 5-20
tailoring, 2-3	training devices, C-1 through C-4
target	training set, fire observation (TSFO), C-2
describing a, E-1 through E-4	trajectory (method of engagement), 4-4, 5-6
description (CFF element), 4-3, 5-7	transmission
equivalents for mnemonics, B-38 number (element of MTO), 4-6	authentication table, 4-7
size and shape, 4-3	method of authentication, 4-7
types (TACFIRE), E-1 through E-3	trees, using to estimate distance, 3-6
target acquisition and designation sight (AH-64), A-14,	trigger point, 5-25
A-15	TSFO-G/VLLD simulation enhancement, C-2
target analysis and munitions effects, E-1 through E-6	
observer responsibilities in, E-1	units to fire (element of MTO), 4-6
TACFIRE target types, E-1 through E-3	unobserved spottings, 5-3
target location	USAF laser systems, A-16
element of call for fire, 4-2	
error, 1-5	vertical shift, determining, 3-2, 3-3
FISTV, determining with, D-2 methods of, 3-1, 4-2	volume of fire (method of engagement), 4-4, 5-7
OF fan, determining with, 3-10	VT fuze, use with HE, 4-10
target posture, 1-3	, , , , , , , , , , , , , , , , , , , ,
targets of opportunity for Copperhead, 6-24 through 6-26	Warning order (CEE alament) 4.1
terrain-map association, 3-1	warning order (CFF element), 4-1
terrain sketch, 3-8	white phosphorus, shell, 4-11
torrain sactor, 5°0	wind speed, methods of determining, 6-16